



## Technical Data Sheet - TimberTech Grading Oak Multiplex Flooring

Characteristics	Markant	Natur	Select
Healthy Sapwood	Permitted	Occasionally Permitted	Not Permitted
Branches	Unlimited Permitted	Up to 30 mm Diameter	Occasional point branches up to approx. 4 mm permissible
Wind Cracks	99% of the planks must be free of Wind Cracks	99% of the planks must be free of Wind Cracks	99% of the planks must be free of Wind Cracks
End Cracks	Occasionally permissible up to approx. 150 mm	Permissible up to approx. 50 mm	Occasionally permissible up to approx. 20 mm
Bark Pockets	Occasionally Permitted	Occasionally Permitted	Not Permitted
Healthy Core	Permitted	Occasionally Permitted	Occasionally Permitted
Wood Stature	Different Fibre Path Permitted	Different Fibre Path Permitted	Different Fibre Path Permitted
Colour Differences	Permitted	Permitted	Permitted
Filled Knots	Permitted	Permitted	Occasionally Permitted
Surface Cracks	Permitted	Occasionally Permitted	Occasionally Permitted
Hairline Cracks	Permitted	Permitted	Permitted
Stacking Slats Patch	Permitted	Not permitted	Not Permitted
Mark Ray	Permitted	Permitted	Permitted
Pest Infestation	Not Permitted	Not Permitted	Not Permitted
			
3% of the planks in a delivery may differ from the respective sorting. Planks that have characteristics other than those listed here are permitted provided the overall appearance is not affected.			